## NSN 6680-00-930-2579

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-930-2579 **Thread Class:** 2b both ends **Thread Direction:** Right-hand both ends **Overall Length:** Between 5.920 inches and 6.300 inches Tip Length: 0.620 inches and 0.880 inches first end **Core Material:** Steel, spring **Screw Thread Series Designator:** Uns first end **Core Diameter:** 0.150 inches **End Type:** Square male second end **End Connection Type:** Threaded internal both ends Setscrew: Not included both ends **Casing Material:** Steel **Wrenching Facility Type:** Serrated surface both ends **Cross Section Size And Location:** 0.201 inches diameter and 0.205 inches diameter first end **Machined Feature Size:** 0.039 in. To 0.045 in. H by 0.058 in. To 0.063 in w drive key **Casing Surface Treatment:** Galvanized **Casing Length Between Ferrules:** 5.000 inches **Casing Outside Diameter:** 0.445 inches Swivel End: Not provided both ends **Enddiameter:** 0.875 inches second end **Lubrication Fitting:** Not provided both ends

Corelength:

Between 5.920 inches and 6.300 inches

## NSN 6680-00-930-2579

Flexible Shaft Assembly - Page 2 of 2



Core Removability:
Removable
Minimum Operating Radius:
5.000 inches
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

T246-e