Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-949-0318

Overall Length: 22.250 inches Media For Which Designed: Air Inlet Connection Type: Threaded **Integral Relief Valve:** Not included Meter Type: Float **Design Type:** Case Unit Type: Mounted Scale Quantity: 1 **Construction:** Side plate **Outlet Connection Type:** Threaded Scale Marking: Scfm Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method: Direct line Carrying Handle:** Not included Dial Scale Marking Range: +4.9/+49.5 **Outlet Connection Size:** 1 in. Npt Base: Not included Float Type: Guided Float Material: Aluminum

NSN 6680-00-949-0318

Flow Rate Indicating Meter - Page 2 of 2



Guide Type: High, capacity fluted guide **Integral Heat Source:** Not included Maximum Working Pressure: 200.0 pounds per square inch **Inlet Connection Size:** 1 in. Npt **Metering Tube Quantity:** 1 **Dial Scale Smallest Increment:** 4.95 scfm **Dial Scale Reference Pointer:** Not included **Spinning Float:** Not included **Integral Pulsation Dampener:** Not included Inlet Connection Position For Which Designed: Horizontal Inlet Connection Device Type: Stationary **Outlet Connection Position For Which Designed:** Horizontal **Outlet Connection Device Type:** Stationary Alarm Signal: Not included **Special Features:** Meter size no. 6hcfb type 18410 with steel end fittings, neoprene packing and neoprene asbestos gaskets, aluminum type no. 62k float, 14.7 psia and 70 degrees f **Reference Number Differentiating Characteristics:** Feat Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: T134-t