NSN 6680-00-950-6129

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-950-6129 **Overall Length:** 20.125 inches Media For Which Designed: Air **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Lb per min Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.10/+2.15 **Outlet Connection Size:** 1/2 in. Npt Base: Not included Float Type: Guided

Float Material: Steel, stainless

NSN 6680-00-950-6129

Flow Rate Indicating Meter - Page 2 of 2



Guide Type:
Fluted tube
Integral Heat Source:
Not included
Maximum Working Pressure:
300.0 pounds per square inch
Inlet Connection Size:
1/2 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
0.05ppm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Apsj, ateq, ackl, astw, bhby, cpzj, cpzk, awae, bjdm, cpzm, and bhsq
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t