NSN 6680-00-953-8945

Overall Length: 2.000 inches

Inlet Connection Type:

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-953-8945

Flange
Integral Relief Valve:
Not included
Indicator Type:
Sight window set directly in tube
Meter Type:
Float
Design Type:
Case or glass
Unit Type:
Mounted
Scale Quantity:
2
Construction:
Inclosed w/sight window
Outlet Connection Type:
Flange
Float Quantity:
2
Tube Material:
Tube Material: Glass
Glass
Glass Mounting Method:
Glass Mounting Method: Direct line
Glass Mounting Method: Direct line Carrying Handle:
Glass Mounting Method: Direct line Carrying Handle: Not included
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range:
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range: +0.0/+100.0
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range: +0.0/+100.0 Base:
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range: +0.0/+100.0 Base: Not included
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range: +0.0/+100.0 Base: Not included Float Type:
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range: +0.0/+100.0 Base: Not included Float Type: Free
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range: +0.0/+100.0 Base: Not included Float Type: Free Float Material:
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range: +0.0/+100.0 Base: Not included Float Type: Free Float Material: Beryllium copper
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range: +0.0/+100.0 Base: Not included Float Type: Free Float Material: Beryllium copper Integral Heat Source:
Glass Mounting Method: Direct line Carrying Handle: Not included Dial Scale Marking Range: +0.0/+100.0 Base: Not included Float Type: Free Float Material: Beryllium copper Integral Heat Source: Not included

NSN 6680-00-953-8945

Flow Rate Indicating Meter - Page 2 of 2



Dial Scale Reference Pointer:
Not included
Float Quantity Per Tube:
1
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Vertical
Alarm Signal:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t