NSN 6680-00-958-9425

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-958-9425



Overall Length: 7.750 inches Media For Which Designed: Water **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Side plate **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +1.0/+15.0 **Outlet Connection Size:** 1 in. Nptf Base: Not included Float Type: Free

Float Material: Steel, stainless

NSN 6680-00-958-9425

Flow Rate Indicating Meter - Page 2 of 2



| Integral Heat Source: |
|---|
| Not included |
| Maximum Working Pressure: |
| 200.0 pounds per square inch |
| Inlet Connection Size: |
| 1 in. Nptf |
| Metering Tube Quantity: |
| 1 |
| Dial Scale Smallest Increment: |
| 1gpm |
| Dial Scale Reference Pointer: |
| Not included |
| Spinning Float: |
| Not included |
| Integral Pulsation Dampener: |
| Not included |
| Inlet Connection Position For Which Designed: |
| Vertical |
| Outlet Connection Position For Which Designed: |
| Vertical |
| Alarm Signal: |
| Not included |
| Reference Number Differentiating Characteristics: |
| As differentiated by dial scale marking range |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |
| Demilitarization: |
| Demilitarization: No |
| |