

View Online at <https://aerobasegroup.com/nsn/6680-00-973-2998>

Current Type:

Ac

Ac Voltage Rating:

Between 105.0 volts and 125.0 volts

Frequency Rating:

Between 320.0 hertz and 480.0 hertz

End Application:

T-38 acft

Electrical Connection Quantity:

2

Indicator Quantity:

1

Special Features:

Master and repeater indicator set that indicates liquid oxygen quantity; t.O.15x4-3 series; dial case per ms33558; case length 5.0 inches for master indicator; case length for repeater indicator 3.5 inches; capacitance for zero reading 123.5 picofarad; weight of master indicator 1.5 lbs; weight of repeater indicator 0.75 lbs; dial diameter 2.0 inches; inside dial diameter 1.812 inches; dial marked liquid oxygen liters, 0 to 10 liters; dial has white lighting; off flag; master indicator connector amphenol p/n 182-2-1000 except face seal in accordance with p/n 67-2058-1868 or equal; master indicator mating connector p/n 165-62; repeater indicator connector amphenol p/n 182-11 or equal; repeater indicator mating connector p/n 165-10; accuracy per mil-I-25645; power 105 to 125 vac, 320 to 480 hz; presentation type: dial; scale range: 0.0 - 10.0 liters

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A534t0