## NSN 6680-00-973-8359

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-00-973-8359



**Overall Length:** 21.390 inches Media For Which Designed: Lubricating oil **Inlet Connection Type:** Threaded Dial Range: +0.2/+3.5 **Integral Relief Valve:** Not included **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.2/+3.4 **Outlet Connection Size:** 3/4 in. lps Base: Not included Float Type: Guided Float Material: Steel, corrosion resisting

## NSN 6680-00-973-8359

Flow Rate Indicating Meter - Page 2 of 2



Guide Type:
Beaded tube
Integral Heat Source:
Not included
Maximum Working Pressure:
200.0 pounds per square inch
Inlet Connection Size:
3/4 in. lps
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
0.02 gpm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Cpzf, awgj, apsj, ateq, ackl, astw, bhby, aewh, cpzj, cpzk; w/scale calibrated for mil-I-7808c at 95 degrees f
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t