NSN 6680-00-973-8361

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-00-973-8361 **Overall Length:** 20.880 inches Media For Which Designed: Air **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Cfm Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Flush panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.3/+3.0 **Outlet Connection Size:** 0.500 in. lps Base: Not included Float Type: Guided Float Material:

Steel, corrosion resisting

Guide Type:Beaded tube

NSN 6680-00-973-8361

Flow Rate Indicating Meter - Page 2 of 2



Integral Heat Source:
Not included
Maximum Working Pressure:
350.0 pounds per square inch
Inlet Connection Size:
0.500 in. lps
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
0.02 cfm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Reference Number Differentiating Characteristics:
Cpzf, awgj, apsj, ateq, ackl, astw, bhby, cpzj, cpzk; w/scale calibrated at 70.0 degrees f and 25.0 psig
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t