NSN 6680-01-045-3361

Overall Length: 4.812 inches

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-045-3361

| Media For Which Designed: |
|--------------------------------|
| Air or gas or liquid |
| Inlet Connection Type: |
| Threaded |
| Integral Relief Valve: |
| Not included |
| Meter Type: |
| Float |
| Design Type: |
| Case |
| Unit Type: |
| Mounted |
| Scale Quantity: |
| 1 |
| Construction: |
| Inclosed w/sight window |
| Outlet Connection Type: |
| Threaded |
| Scale Marking: |
| Scfm air |
| Scale Type: |
| Direct capacity reading |
| Float Quantity: |
| 1 |
| Tube Material: |
| Plastic |
| Mounting Method: |
| Flush panel or surface panel |
| Carrying Handle: |
| Not included |
| Dial Scale Marking Range: |
| +10.0/+100.0 |
| Outlet Connection Size: |
| 0.125 in. Npt |
| Base: |
| Not included |
| Float Type: |
| Guided |
| Float Material: |
| Steel, stainless |

NSN 6680-01-045-3361

Flow Rate Indicating Meter - Page 2 of 2



| Guide Type: |
|--|
| Beaded tube |
| Integral Heat Source: |
| Not included |
| Maximum Working Pressure: |
| 100.0 pounds per square inch |
| Inlet Connection Size: |
| 0.125 in. Npt |
| Metering Tube Quantity: |
| 1 |
| Dial Scale Smallest Increment: |
| 5cc |
| Dial Scale Reference Pointer: |
| Not included |
| Spinning Float: |
| Not included |
| Integral Pulsation Dampener: |
| Not included |
| Inlet Connection Position For Which Designed: |
| Horizontal |
| Inlet Connection Device Type: |
| Stationary |
| Outlet Connection Position For Which Designed: |
| Horizontal |
| Outlet Connection Device Type: |
| Stationary |
| Alarm Signal: |
| Not included |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T134-t |