NSN 6680-01-081-8743



Flow Rate Indicating Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-01-081-8743 **Overall Length:** 9.813 inches **Inlet Connection Type:** Threaded **End Application:** 4920-01-053-2833 test stand **Integral Relief Valve:** Not included **Indicator Type:** Ball float **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Open post w/protection shield **Outlet Connection Type:** Threaded Scale Type: Millimeter reference reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Direct line or flush panel or surface panel **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.0/+175.0 **Outlet Connection Size:** 0.250 or 0.125 in. Npt Base: Not included Float Type: Guided Float Material:

Steel, stainless or glass or sapphire or tantalum or tungsten carbide

NSN 6680-01-081-8743

Flow Rate Indicating Meter - Page 2 of 2



Guide Type:
Fluted tube
Integral Heat Source:
Not included
Maximum Working Pressure:
200.0 pounds per square inch
Inlet Connection Size:
0.250 or 0.125 in. Npt
Metering Tube Quantity:
1
Maximum Water Capacity In Gallons Per Minute:
0.5
Maximum Air Capacity In Cubic Feet Per Minute:
2.2
Dial Scale Smallest Increment:
1mm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
T134-t