

View Online at <https://aerobasegroup.com/nsn/6680-01-082-4842>

**Overall Length:**

9.813 inches

**Inlet Connection Type:**

Threaded

**End Application:**

4920-01-053-2833 test stand

**Integral Relief Valve:**

Not included

**Indicator Type:**

Ball float

**Design Type:**

Case

**Unit Type:**

Mounted

**Scale Quantity:**

1

**Construction:**

Open post w/protection shield

**Outlet Connection Type:**

Threaded

**Scale Type:**

Millimeter reference reading

**Float Quantity:**

1

**Tube Material:**

Glass

**Mounting Method:**

Direct line or flush panel or surface panel

**Carrying Handle:**

Not included

**Dial Scale Marking Range:**

+0.0/+175.0

**Outlet Connection Size:**

0.250 or 0.125 in. Npt

**Base:**

Not included

**Float Type:**

Guided

**Float Material:**

Steel, stainless or glass or sapphire or tantalum or tungsten carbide

**Guide Type:**

Fluted tube

**Integral Heat Source:**

Not included

**Maximum Working Pressure:**

200.0 pounds per square inch

**Inlet Connection Size:**

0.250 or 0.125 in. Npt

**Metering Tube Quantity:**

1

**Maximum Water Capacity In Gallons Per Minute:**

0.5

**Maximum Air Capacity In Cubic Feet Per Minute:**

2.2

**Dial Scale Smallest Increment:**

1mm

**Dial Scale Reference Pointer:**

Not included

**Spinning Float:**

Not included

**Integral Pulsation Dampener:**

Not included

**Inlet Connection Position For Which Designed:**

Horizontal

**Inlet Connection Device Type:**

Stationary

**Outlet Connection Position For Which Designed:**

Horizontal

**Outlet Connection Device Type:**

Stationary

**Alarm Signal:**

Not included

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T134-t