Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-098-9682

4 Freminal Type: Stud Overall Length: 63.750 inches Current Type: Diate Current Type: Diate Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Float Cannon electric Partical Connection Identifying Number: Parta 36468 Mouning Method: Bracket Shelf Life: Na Did Of Measure: r r Fig: Na Fig: Na Fig: Fig: Fig: Fig: Fig: Fig: Fig:	Tern	ninal Quantity:
StudOverall Length:63.750 inchesCurrent Type:DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketShelf Life:N/aLife:N/aFing:NoFing:		
Overall Length:63.750 inchesCurrent Type:DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1FloatPart no. 36468Mounting Method:BracketShelf Life:NaLint Of Measure:Image: Name:NaFig:NaFig:Fig:	Tern	ninal Type:
63.750 inchesCurrent Type:DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:11Electrical Connection Controlling Agency:Cannon electricPart no. 36468Mounting Method:BracketShelf Life:NaUnit of Measure:TPanilitarization:NoFig:	Stud	
Current Type:DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketShelf Life:N/aInt Of Measure:TNaFig:Fig:	Ove	rall Length:
Dc Atachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Uit Of Measure: Panilitarization: No Fig:	63.7	50 inches
Attachment Feature Quantity: 2 Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Sheff Life: N/a Inf Of Measure: - Pamilitarization: No Fig:	Curr	rent Type:
2 Actuation Method: Float Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Sheff Life: N/a Sheff Life: N/a Dinifor Measure: 	Dc	
Actuation Method:FloatFloatVoltage Rating:Between 10.0 volts and 12.0 voltsBetween 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Bettrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketShelf Life:N/aInit of Measure:Pamilitarization:NoFig:	Atta	chment Feature Quantity:
Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: I 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Init Of Measure: Poinlitarization: No Fig:	2	
Voltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:11Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketShelf Life:Iv/aUnit Of Measure:NoFig:	Actu	lation Method:
Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: Iva Dunt of Measure: Demilitarization: No Fig:	Floa	t
Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Paraket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Volta	age Rating:
1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Part no. 36468 Mounting Method: Bracket Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Betw	veen 10.0 volts and 12.0 volts
Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketBracketShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Elec	trical Connection Quantity:
Canon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1	
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Elec	trical Connection Controlling Agency:
Part no. 36468 Mounting Method: Bracket Bracket N/a Unit Of Measure: Pemilitarization: No Fig:	Canı	non electric
Mounting Method:BracketBracketShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Elec	trical Connection Identifying Number:
Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Part	no. 36468
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
N/a Unit Of Measure: Demilitarization: No Fiig:		
Unit Of Measure: Demilitarization: No Fiig:		If Life:
 Demilitarization: No Fiig:		
Demilitarization: No Fiig:	Unit	Of Measure:
No Fiig:		
Fiig:		ilitarization:
T145-b		
	T145	5-b