Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-098-9690

3         Ferninal Type:         Stud         Overall Length:         106.750 inches         Current Type:         Dc         Attachment Feature Quantity:         2         Actuation Method:         Float         Voltage Rating:         Between 10.0 volts and 12.0 volts         Electrical Connection Quantity:         1         Float         Voltage Rating:         Cannon electric         Electrical Connection Identifying Number:         Part no. 36468         Mouting Method:         Brackt         Shelf Life:         Na         Unit Of Measure:         r         For         Functional Consection Life State         Functional Consection Life State         Functional Consection Life State         Shelf Life:         Na         Duit Of Measure:         r         Fig:         Functional Consection Life State         Shelf Life:         Shelf Life:         Shelf Life:         Shelf Life:         Shelf Life:         Shelf Life: <th>Terminal Quantity:</th>	Terminal Quantity:
Stud   Overall Length:   106.750 inches   Current Type:   Dc   Attachment Feature Quantity:   2   Actuation Method:   Float   Voltage Rating:   Between 10.0 volts and 12.0 volts   Electrical Connection Quantity:   1   Electrical Connection Controlling Agency:   Cannon electric   Electrical Connection Identifying Number:   Part no. 36468   Mounting Method:   Bracket   Sheff Life:   Na   Fig:	3
Overall Length:106.750 inchesCurrent Type:DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Quantity:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:StacketSheff Life:NaInit of Measure:NaFormilitarization:NoFig:	Terminal Type:
106,750 inchesCurrent Type:DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:Sheff Life:N/aDirit of Measure:rNaFing:Fing:	Stud
Current Type:DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:IsracketShelf Life:IvaDrilt of Measure:IvaFig:NoFig:	Overall Length:
Dc         Attachment Feature Quantity:         2         Actuation Method:         Float         Voltage Rating:         Between 10.0 volts and 12.0 volts         Electrical Connection Quantity:         1         Electrical Connection Quantity:         Cannon electric         Part no. 36468         Mounting Method:         Packet         Shelf Life:         Na         Dit Of Measure:         I         Pointilarization:         No         Fig:	106.750 inches
Attachment Feature Quantity:         2         Actuation Method:         Float         Voltage Rating:         Between 10.0 volts and 12.0 volts         Electrical Connection Quantity:         1         Electrical Connection Controlling Agency:         Cannon electric         Part no. 36468         Mounting Method:         Bracket         Shelf Life:         N/a         Dird f Measure:         -         Pomilitarization:         No         Fig:	Current Type:
2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Parket Shelf Life: Na Unit Of Measure: - Deniltarization: No Fig:	Dc
Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:11Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketShelf Life:N/aUnit Of Measure:NoFig:	Attachment Feature Quantity:
Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: Cannon electric Electrical Connection Identifying Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	2
Voltage Rating:         Between 10.0 volts and 12.0 volts         Electrical Connection Quantity:         1         Electrical Connection Controlling Agency:         Cannon electric         Electrical Connection Identifying Number:         Part no. 36468         Mounting Method:         Bracket         Shelf Life:         N/a         Unit Of Measure:            Pomilitarization:         No         Fig:	Actuation Method:
Between 10.0 volts and 12.0 volts         Electrical Connection Quantity:         1         Electrical Connection Controlling Agency:         Cannon electric         Electrical Connection Identifying Number:         Part no. 36468         Mounting Method:         Bracket         Sheff Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Float
Electrical Connection Quantity:   1   Electrical Connection Controlling Agency:   Cannon electric   Electrical Connection Identifying Number:   Part no. 36468   Mounting Method:   Bracket   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Voltage Rating:
1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Between 10.0 volts and 12.0 volts
Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Bracket Shelf Life: N/a Unit Of Measure:  Pomilitarization: No	Electrical Connection Quantity:
Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Pomilitarization: No Fig:	1
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Electrical Connection Controlling Agency:
Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Cannon electric
Mounting Method:BracketBracketShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Electrical Connection Identifying Number:
Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Part no. 36468
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Mounting Method:
N/a Unit Of Measure: Demilitarization: No Fiig:	Bracket
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
T145-b	
	Т145-b