## NSN 6680-01-103-0377

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-103-0377

Overall Length:
10.000 inches
Media For Which Designed:
Gas
Inlet Connection Type:
Threaded
End Application:
Vitok engineering co, co2 removal plant
Integral Relief Valve:
Not included
Indicator Type:
Float magnetically coupled to scale pointer
Meter Type:
Float
Design Type:
Case
Unit Type:
Mounted
Scale Quantity:
1
Construction:
Inclosed w/sight window
Outlet Connection Type:
Threaded
Scale Marking:
Lb per hr
Scale Type:
Direct capacity reading
Float Quantity:
1
Tube Material:
Steel, federal standard 66, aisi 316/sae 30316
Mounting Method:
Direct line
Carrying Handle:
Not included
Dial Scale Marking Range:
+3.4/+34.0
Outlet Connection Size:
0.500 in. Npt
Rase.

Not included

## NSN 6680-01-103-0377

Flow Rate Indicating Meter - Page 2 of 2



Float Type:
Guided
Float Material:
Steel, federal standard 66, aisi 316/sae 30316
Guide Type:
Solid rod
Integral Heat Source:
Not included
Maximum Working Pressure:
1500.0 pounds per square inch
Inlet Connection Size:
0.500 in. Npt
Metering Tube Quantity:
1
Dial Scale Reference Pointer:
Included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Vertical
Outlet Connection Position For Which Designed:
Vertical
Alarm Signal:
Not included
Special Features:
Calibrated in lbs perhour of carbon dioxide gas at 25 psig and 70 degrees f; serial no. 7411 a 0421 a1-2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t