Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-113-8030

3 Terminal Type: Stud Overall Length: 106.750 inches Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Sheff Life: Na Uht Of Measure: Demilitarization: No Fiig: Tut5-b	Terminal Quantity:
Terminal Type:StudOverall Length:105.750 inchesCurrent Type:DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricPart no. 36468Mounting Method:Part no. 36468Mounting Method:NaViaNaPine:NoFlig:	
Stud Overall Length: 106.750 inches Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Part no. 36468 Mounting Method: Part no. 36468 Mounting Method: Iracket Sheff Life: Na Dut Of Measure: r Ponilitarization: No Fig:	
Overall Length:106.750 inchesCurrent Type:DcAttachment Feature Quantity:2Actuation Method:FloatVotage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketShelf Life:N/aInt Of Measure:-Penilitarization:NoFig:	
108.750 inches Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36488 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: - Pemilitarization: No Fig:	
Current Type:DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:11Electrical Connection Controlling Agency:Cannon electricPart no. 36468Mounting Method:BracketSheff Life:NaInt of Measure:-Part no. 10 Measure:NoFig:	
DcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricPart no. 36468Mounting Method:BracketSheff Life:Na-Part no. 36468Munting Method:BracketSheff Life:NaFig:NoFig:	
2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: Cannon electric Cannon electric Electrical Connection Identifying Number: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Sheff Life: N/a District Measure: - Demilitarization: No Fig:	
2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: Cannon electric Cannon electric Electrical Connection Identifying Number: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Sheff Life: N/a District Measure: - Demilitarization: No Fig:	Attachment Feature Quantity:
Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Betwein electric Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Fig:	
Voltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Actuation Method:
Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Float
Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Paracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Voltage Rating:
1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 10.0 volts and 12.0 volts
Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Electrical Connection Quantity:
Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Shelf Life: N/a Unit Of Measure: Pemilitarization: No Fig:	Electrical Connection Controlling Agency:
Part no. 36468Mounting Method:BracketShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Cannon electric
Mounting Method:BracketShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Electrical Connection Identifying Number:
Bracket Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Part no. 36468
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Method:
N/a Unit Of Measure: Demilitarization: No Fiig:	Bracket
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
T145-b	Fiig:
	T145-b