

NSN 6680-01-113-9147 Flow Rate Indicating Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-01-113-9147 **Overall Length:** 5.125 inches Media For Which Designed: Air **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Accessory Components And Quantity:** Lower center front needle valve, 1 **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Cubic feet per hour Scale Type: Direct capacity reading Float Quantity:

Tube Material:

Plastic

Mounting Method:

Flush panel

Carrying Handle:

Not included

Dial Scale Marking Range:

+20.0/+225.0

Outlet Connection Size:

0.250 in. Npt

Base:

Not included

Float Type:

Free

NSN 6680-01-113-9147

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Steel, stainless
Integral Heat Source:
Not included
Maximum Working Pressure:
100.0 pounds per square inch
Inlet Connection Size:
0.250 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
20 cu ft
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Buna n o rings
Reference Number Differentiating Characteristics:
As differentiated by accessory components and quantity
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t