NSN 6680-01-115-1498

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-115-1498

| Media For Which Designed: |
|-------------------------------|
| Ethylene or water |
| Inlet Connection Type: |
| Threaded |
| Integral Relief Valve: |
| Not included |
| Meter Type: |
| Float |
| Design Type: |
| Case |
| Unit Type: |
| Mounted |
| Scale Quantity: |
| 1 |
| Construction: |
| Inclosed w/sight window |
| Outlet Connection Type: |
| Threaded |
| Scale Marking: |
| Gallons per minute |
| Scale Type: |
| Direct capacity reading |
| Mounting Method: |
| Direct line |
| Carrying Handle: |
| Not included |
| Dial Scale Marking Range: |
| +0.3/+3.0 |
| Outlet Connection Size: |
| 0.500 in. Npt |
| Base: |
| Not included |
| Integral Heat Source: |
| Not included |
| Maximum Working Pressure: |
| 200.0 pounds per square inch |
| Inlet Connection Size: |
| 0.500 in. Npt |
| Dial Scale Reference Pointer: |
| Not included |
| Inlet Connection Device Type: |
| Stationary |

NSN 6680-01-115-1498

Flow Rate Indicating Meter - Page 2 of 2



| Outlet Connection Position For Which Designed: |
|--|
| Horizontal |
| Outlet Connection Device Type: |
| Stationary |
| Alarm Signal: |
| Not included |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . - |
| Demilitarization: |
| No |

Fiig: T134-t