## NSN 6680-01-116-8173

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-116-8173 **Overall Length:** 8.750 inches Media For Which Designed: Air **Inlet Connection Type:** Threaded **End Application:** 4935-01-103-6424 leak detector **Integral Relief Valve:** Included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 Illuminative Method: Any acceptable **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Scfh air Scale Type: Direct capacity reading Float Quantity: **Tube Material: Plastic Mounting Method:** Flush panel or surface panel **Dial Scale Marking Range:** 

**Carrying Handle:** Not included **Unit Location:** Right center front +10.0/+100.0 **Outlet Connection Size:** 0.250 in. Npt

## NSN 6680-01-116-8173

Flow Rate Indicating Meter - Page 2 of 2



Base:
Not included
Float Type:
Guided
Float Material:
Glass
Guide Type:
Any acceptable
Integral Heat Source:
Not included
Maximum Working Pressure:
70.0 pounds per square inch
Inlet Connection Size:
0.250 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
10.0 scfh
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t