NSN 6680-01-122-2654

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-122-2654 **Overall Length:** 18.250 inches Media For Which Designed: Air **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Open post w/protection shield **Outlet Connection Type:** Threaded Scale Marking: Lb per min Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.0624/+0.6240 **Outlet Connection Size:** 0.500 in. Npt Base: Not included Float Type: Guided

Float Material: Steel, stainless

NSN 6680-01-122-2654

Flow Rate Indicating Meter - Page 2 of 2



| Guide Type: |
|---|
| Beaded tube |
| Integral Heat Source: |
| Not included |
| Maximum Working Pressure: |
| 75.0 pounds per square inch |
| Inlet Connection Size: |
| 0.500 in. Npt |
| Metering Tube Quantity: |
| 1 |
| Dial Scale Smallest Increment: |
| Any acceptable |
| Dial Scale Reference Pointer: |
| Not included |
| Spinning Float: |
| Not included |
| Integral Pulsation Dampener: |
| Not included |
| Inlet Connection Position For Which Designed: |
| Horizontal |
| Inlet Connection Device Type: |
| Stationary |
| Outlet Connection Position For Which Designed: |
| Horizontal |
| Outlet Connection Device Type: |
| Stationary |
| Alarm Signal: |
| Not included |
| Special Features: |
| Inlet and outlet connections spaced 16.500 in. C to c |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T134-t |