## NSN 6680-01-122-2654

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-122-2654 **Overall Length:** 18.250 inches Media For Which Designed: Air **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Open post w/protection shield **Outlet Connection Type:** Threaded Scale Marking: Lb per min Scale Type: Direct capacity reading Float Quantity: 1 **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.0624/+0.6240 **Outlet Connection Size:** 0.500 in. Npt Base: Not included Float Type: Guided

Float Material: Steel, stainless

## NSN 6680-01-122-2654

Flow Rate Indicating Meter - Page 2 of 2



Guide Type:
Beaded tube
Integral Heat Source:
Not included
Maximum Working Pressure:
75.0 pounds per square inch
Inlet Connection Size:
0.500 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
Any acceptable
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Inlet and outlet connections spaced 16.500 in. C to c
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t