

NSN 6680-01-125-6516 Liquid Volumetric Positive Displacement Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-01-125-6516 **Body Material:** Bronze **Maximum Operating Pressure:** 50.0 pounds per square inch Media For Which Designed: Water, hot **Inlet Connection Type:** Threaded **Maximum Operating Temp:** 180.0 degrees fahrenheit Installation Design: Direct mount **Inlet Connection Size:** 1.000 in. lps **Measurement Unit:** Gallon Scale Measurement Range: +0.0/+999999.9 **Outlet Connection Type:** Threaded **Displacement Type:** Disk **Installation Location:** Any acceptable **Liquid Flow Rate:** 18.0 gallons per minute **Register Type:** Wheel

**Reset Feature:** 

Not provided

**Printing Mechanism:** 

Not provided

**Inlet Union Connection:** 

Provided

**Outlet Connection Size:** 

1.0 in. ld

**Outlet Union Connection:** 

Provided

**Precious Material And Location:** 

Connections silver

**Precious Material:** 

Silver

## NSN 6680-01-125-6516

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T134-d