

NSN 6680-01-126-5031 Flow Rate Indicating Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-01-126-5031 **Overall Length:** 10.125 inches Media For Which Designed: Gas **Inlet Connection Type:** Threaded **End Application:** Sperry corporation defense products group, liquid fuel tank **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 Illuminative Method: Any acceptable **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Std cu fpm Scale Type: Direct capacity reading Float Quantity:

**Tube Material:** 

Glass

**Mounting Method:** 

Direct line

**Carrying Handle:** 

Not included

**Dial Scale Marking Range:** 

+0.000/+0.018

**Outlet Connection Size:** 

0.250 in. Npt

Base:

Not included

## NSN 6680-01-126-5031

Flow Rate Indicating Meter - Page 2 of 2



Float Type:
Free
Float Material:
Glass
Integral Heat Source:
Not included
Maximum Working Pressure:
19.1 pounds per square inch
Inlet Connection Size:
0.250 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
0.0005 standard cu fpm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Serial no. 7404-72186/1
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T13/Lt