NSN 6680-01-127-7878

Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-127-7878 **Body Material:** Aluminum **Maximum Operating Pressure:** 150.0 pounds per square inch Media For Which Designed: 0il **Inlet Connection Type:** Threaded **Maximum Operating Temp:** 200.0 degrees fahrenheit **Accessory Components And Quantity:** Air eliminator, 1; strainer, 1 Installation Design: Direct mount **Inlet Connection Size:** 2.000 in. lps **Measurement Unit:** Gallon Scale Measurement Range: +0.0/+99999.0 **Outlet Connection Type:** Threaded **Displacement Type:** Rotor **Installation Location:** Any acceptable **Liquid Flow Rate:** Between 10.0 gallons per minute and 100.0 gallons per minute **Register Type:** Wheel **Reset Feature:** Provided **Printing Mechanism:** Not provided **Inlet Union Connection:** Not provided **Outlet Connection Size:** 2.000 in. lps **Outlet Union Connection:**

Not provided Shelf Life:

N/a

NSN 6680-01-127-7878

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

T134-d