## NSN 6680-01-151-4000

Flexible Shaft Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-151-4000

| Thread Class:  |
|--|
| 2b second end  |
| Thread Direction:  |
| Right-hand second end                                      |
| Thread Length:   |
| 0.375 inches second end                                    |
| Overall Length:  |
| Between 86.054 inches and 86.196 inches                    |
| Wrenching Facility Outside Diameter:                       |
| 0.750 inches second end                                    |
| Tip Length:  |
| 0.972 inches second end                                    |
| Core Material:   |
| Any acceptable   |
| Screw Thread Series Designator:                            |
| Uns first end  |
| Core Diameter:   |
| Between 0.128 inches and 0.152 inches                      |
| Thread Location:   |
| Internal second end  |
| End Type:  |
| Square male first end                                      |
| Width Across Flats:  |
| 1.000 inches first end                                     |
| End Connection Type:                                       |
| Threaded internal second end                               |
| Casing Material:   |
| Plastic  |
| Wrenching Facility Type:                                   |
| Hexagon second end   |
| Cross Section Size And Location:                           |
| 0.150 inches diameter and 0.153 inches diameter second end |
| Casing Surface Treatment:                                  |
| Any acceptable   |
| Casing Length Between Ferrules:                            |
| 85.000 inches  |
| Casing Outside Diameter:                                   |
| Between 0.300 inches and 0.500 inches                      |
| Casing Protective Device Type:                             |
| Plastic cover  |
| Swivel End:  |
| Not provided second end                                    |

## NSN 6680-01-151-4000

Flexible Shaft Assembly - Page 2 of 2



Enddiameter:

1.000 inches first end

**Lubrication Fitting:** 

Not provided second end

Corelength:

86.156 inches

**Core Rotation Direction:** 

Clockwise

Core Removability:

Removable

Minimum Operating Radius:

5.000 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T246-e