NSN 6680-01-168-2536

Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-168-2536

Terminal Quantity:
3
Terminal Type:
Stud
Overall Length:
38.750 inches
Current Type:
Dc
Attachment Feature Quantity:
1
Actuation Method:
Float
Voltage Rating:
Between 10.0 volts and 12.0 volts
Electrical Connection Quantity:
1
Electrical Connection Controlling Agency:
Cannon electric
Electrical Connection Identifying Number:
Part no. 36468
Mounting Method:
Flange
Resistance In Ohms:
Resistance In Ohms: 43.000 per inch of indication
43.000 per inch of indication
43.000 per inch of indication Pressure Rating:
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material:
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel:
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 33.750 inches
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 33.750 inches Media For Which Designed:
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 33.750 inches Media For Which Designed: Water
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 33.750 inches Media For Which Designed: Water Shelf Life:
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 33.750 inches Media For Which Designed: Water Shelf Life: N/a
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 33.750 inches Media For Which Designed: Water Shelf Life: N/a
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 33.750 inches Media For Which Designed: Water Shelf Life: N/a Unit Of Measure:
43.000 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 225.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 33.750 inches Media For Which Designed: Water Shelf Life: N/a Unit Of Measure: Demilitarization: