## NSN 6680-01-174-8157

Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-174-8157 **Body Material:** Aluminum, cast **Maximum Operating Pressure:** 50.0 pounds per square inch Media For Which Designed: Petroleum products **Inlet Connection Type:** Threaded **Maximum Operating Temp:** 165.0 degrees fahrenheit **Accessory Components And Quantity:** Totalizer, 1 Installation Design: Direct mount **Inlet Connection Size:** 1.000 in. Npt **Measurement Unit:** Gallon Scale Measurement Range: +0.0/+100.0 **Outlet Connection Type:** Threaded **Displacement Type:** Any acceptable **Installation Location:** Any acceptable **Liquid Flow Rate:** Between 3.0 gallons per minute and 15.0 gallons per minute **Register Type:** Wheel **Reset Feature:** Provided **Printing Mechanism:** Not provided **Inlet Union Connection:** Not provided **Outlet Connection Size:** 1.000 in. Npt

**Outlet Union Connection:** 

Not provided

**Special Features:** 

Also designed for many other nonviscous industrial liquids

NSN 6680-01-174-8157 Liquid Volumetric Positive Displacement Meter - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

T134-d