NSN 6680-01-197-2904

Liquid Volumetric Positive Displacement Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-197-2904 **Body Material:** Iron, cast **Maximum Operating Pressure:** 150.0 pounds per square inch Media For Which Designed: Liquid **Inlet Connection Type:** Threaded **Maximum Operating Temp:** 93.3 degrees celsius or 200.0 degrees fahrenheit Installation Design: Direct mount **Inlet Connection Size:** 2.000 in. **Measurement Unit:** Gallon Scale Measurement Range: +0.0/+9999.0 **Outlet Connection Type:** Threaded **Displacement Type:** Any acceptable **Installation Location:** Right hand side **Liquid Flow Rate:** Between 24.0 gallons per minute and 120.0 gallons per minute **Register Type:** Wheel **Reset Feature:** Provided **Printing Mechanism:** Not provided **Inlet Union Connection:** Not provided **Outlet Connection Size:** 2.0 in. **Outlet Union Connection:** Not provided

Reference Number Differentiating Characteristics:

As differentiated by serial no. 032-14-0350338

Shelf Life:

N/a

NSN 6680-01-197-2904

Liquid Volumetric Positive Displacement Meter - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

T134-d