Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-198-0039

Terminal Quantity: 3 Terminal Quantity: 3 Terminal Type: Stud Overall Length: 93.750 inches Current Type: Do Attachment Feature Quantity: 2 Attachment Feature Quantity: 3 Hotage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: 1 Electrical Connection Quantity: 1 Electrical Connection Mentifying Number: Part no. 36468 Mounting Method: Biackat Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Heffective Travel: 83.000 inches Medae For Which Designed: Watar Sheff Life: Na Unit of Measure:			
Ferninal Type: Stud Overal Length: 93.750 inches Current Type: De Atachment Feature Quantity: 2 Actachment Feature Quantity: 1 Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Controlling Agency: Cannon electric Restance In Ohms: Scholl per inch of indication Pressure Rating: 400.000 pounds per square inch Float Meterial: Rubber, Jouean Float Gettrice Travel: 8.000 inches Meterial: Nator Material: Nator Nator Nator Nator Nator Nator Nator Nator Scholl Electrice In Compone Sense Rating Nator Scholl Electrice Travel:		inal Quantity:	
Situd Overall Length: S0.750 Inches Current Type: De De Attachment Feature Quantity: 2 Attaction Method: Float Vottage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: 2 Cannon electric Electrical Connection Identifying Number: Part no: 36488 Mouning Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 40000 pounds per square inch Float Herien: Rubber, buen- Float Effective Trave! 83.000 inches Methor: Statel Te: Na Det If Measure: Vital Statel Te: Na Det If Measure: State If			
Overall Length:93.750 inchesCurrent Type:DeAttachment Feature Quantity:2Actuation Method:FloatVotage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricPart no. 36468Mounting Method:5.100 per inch of indicationPressere Rating:00.000 pounds per square inchFloat Effective Travel:83.000 inchesMouting Method:83.000 inchesMode SMode SMode SMode SBio Pr Mich Designed:NaleFloat Effective Travel:83.000 inchesMedia For Mich Designed:NaleDerilitizzation:NaleFloat SModia For Mich Designed:NaleFloat SMaleStrift Fie:NaleFloat SFloat SMaleStrift Fies:NaleFloat SMaleFloat SMaleStrift Fies:Part SStrift Fies:Part SPart SMaleSPart SPart		inal Type:	
93.750 incloses Current Type: Comment Feature Quantity: Catatation Method: Float Float Voltage Rating: Electrical Connection Quantity: Cannon electric Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: 5.100 per inch of indication Pressure Rating: Aduoted in Comment inchestric Electrical Connection Identifying Number: Float Material: Rubber, buna-n Float Method: Float Effective TraveI: Basolo inches Comment inchestric Comment inchest			
Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Stacket Resistance In Ohms: St000 pounds per square inch Pressure Rating: 400.000 pounds per square inch Float Hettrice Trave! St000 pounds per square inch Float Hettrice Trave! Rubber, bun-n Float Hettrice Trave! St000 pounds per square inch Houtify Thio Designed: Water Stoff Life: Na Dieleficitizzion: Na Denilitarization: Float Hettrice Trave! Float Hettrice Trave! Stoff Life: Na Dieleficitizzion:			
Dc Attachment Feature Quantity: 2 Actaction Method: Float Float Votage Rating: Betwen 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Heferitive Travel: 8.000 notes Float Effective Travel: 8.000 notes Part Inc.: Nabure: 9.000 pounds per square inch Float Effective Travel: 8.000 notes Pressure Rating: 4.000 pounds per square inch Float Effective Travel: 8.000 notes Part Inc: Nabure: Batt Inc: Nabure: Part Inc: Part Inc: Nabure: Part Inc: <			
Attachment Feature Quantity: 2 Actuation Method: Float Float Voitage Rating: Between 10.0 voits and 12.0 voits Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Part no. 36468 Mounting Method: Bracket Partical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Robistace In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 83.000 inches Media For Which Designed: Vater Shoff Life: Na Conf Measure: Canone Company Field Measure: Na Denlitarization: No Fig:		ent Type:	
2 Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: I Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Merrial: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: Vater Na Sindon Indensis: Na Sindon Indensis: Na Sindon Indensis: Na Sindon Indensis: Na Sindon Indensis: Sindon			
Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Haterial: Rubber, buna-n Float Effective Travel: 83.000 inches Modia For Which Designed: Vater Shift Life: Na Shift Metasure: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: Vater Shift Life: Na Shift Metasure: Tot Metasure: Tata Float Metasure: Float Shift Metasure: Float Shift Metasure: Na Shift Metasure		hment Feature Quantity:	
Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 83:000 inches Method: Bracket Method: Image: Vater Sheff Life: Na Uit Of Measure: - Panel No Fig:			
Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 83.000 inches Media For Which Designed: Vatar Na Dit Of Measure: · · Prost Iffective Travel: S1.000 inches Media For Which Designed: Vatar Piol Iffe: No Piol Iffective: Nava For Ifficitive: Nava Piol Ifficitive: Nava Ford Ifficitive: Image: Image: Image:	Actuat	ation Method:	
Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: Vater Sheff Life: Na Priot Of Measure: - Fourilitarization: No Fig:			
Ieterical Connection Controlling Agency: Cannon electric Cancon electric Ieterical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: Vater Shelf Life: Na Dint Of Measure: Pomilitarization: No Fig:			
1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: Vater Shelf Life: Na Unit Of Measure: Penilitarization: No Fig:			
Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 83.000 inches Method Part Infe: N/a Diff Infe: N/a Diff Of Measure: r Pomilitarization: No Fig:	Electric	rical Connection Quantity:	
Canon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: Vater Nater Information: Nater Info	1		
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: Vater Shelf Life: N/a Dint of Measure: - Pomilitarization: No Fig:	Electric	rical Connection Controlling Agency:	
Part no. 36468Mounting Method:BracketResistance In Ohms:5.100 per inch of indicationPressure Rating:400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:83.000 inchesMedia For Which Designed:VaterShelf Life:NaDin of Measure:Pomilitarization:NoFig:	Cannor	on electric	
Mounting Method:BracketBrasistance In Ohms:5.100 per inch of indicationPressure Rating:400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:83.000 inchesMedia For Which Designed:VaterShelf Life:IvaDint Of Measure:NoFig:	Electric	rical Connection Identifying Number:	
Bracket Resistance In Ohms: S.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: Rober, Buna-n Broat Effective Travel: Salo0 inches Media For Which Designed: Vater Shelf Life: N/a Unit Of Measure: No No Fig:	Part no	10. 36468	
Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: Vater Shelf Life: N/a Dint Of Measure: Fomilitarization: No Flig:	Mounti	nting Method:	
5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: 400 Media For Which Designed: 400 M	Bracket	.et	
Pressure Rating:400.000 pounds per square inch400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:83.000 inchesMedia For Which Designed:WaterShelf Life:N/aUnit Of Measure:-Penilitarization:NoFiig:	Resista	stance In Ohms:	
400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 83.000 inches Media For Which Designed: Water Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	5.100 p	per inch of indication	
Float Material:Rubber, buna-nFloat Effective Travel:83.000 inchesMedia For Which Designed:WaterShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:	Pressu	sure Rating:	
Rubber, buna-n Float Effective Travel: 83.000 inches Badia For Which Designed: Water Shelf Life: N/a Unit Of Measure: - Pemilitarization: No Fig:	400.000	00 pounds per square inch	
Float Effective Travel:83.000 inchesMedia For Which Designed:WaterShelf Life:N/aUnit Of Measure:Penilitarization:NoFig:	Float N	Material:	
83.000 inches Media For Which Designed: Water Shelf Life: N/a Unit Of Measure: No Shelf Life: No Shelf Life: Sh	Rubber	er, buna-n	
Media For Which Designed: Water Shelf Life: N/a Ditt Of Measure: Demilitarization: No Fig:	Float E	Effective Travel:	
Water Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	83.000	i0 inches	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Media	a For Which Designed:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Water	r	
Unit Of Measure: Demilitarization: No Fiig:	Shelf L	Life:	
 Demilitarization: No Fiig:	N/a		
Demilitarization: No Fiig:	Unit Of	Of Measure:	
No Fiig:			
Fiig:	Demilit	litarization:	
	No		
T145-b	Fiig:		
	T145-b	-b	