Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-200-1798

Terminal Quantity: 4 4 4 6 Ferminal Type: Stud Overall Length: 68.750 inches Current Type: Consection Method: Float Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: Cannon electric Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 38468 Mounting Method: Stracket Resistance in Ohms: S		
Fernihal Type: Stud Overall Length: 68.750 inches Current Type: De Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Canone electric Electrical Connection Identifying Number: Part no. 36468 Mouning Method: Stoole provide and 10.0000 pounds per square inch indication Pressure Rating: Batween 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Ruber, buna-n Float Effective Tavel: Sy 750 inches Media For Which Designed: Oil Shoff Life: Na Child Rusare: Part Inter: Na Child Result Since in A dimention Provet Tavel: Since in A dimention Part Inter: Na Chateria: Since in A dimentin <th>Terminal Quantity:</th> <th></th>	Terminal Quantity:	
Stud Overall Length: 68,750 inches Current Type: De Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Hefective Travel: Syzös inches Media For Which Designed: Oil Sheff Life: Na Chief Maseria: Na Derilitarization: Yas - dentil/mil	4	
Overall Length:68,750 inchesCurrent Type:DeActuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketResistance In Ohms:5.100 per inch of indicationPressure Rating:Between 0.000 pounds per square inch and 400.000 pounds per square inchFloat Hective Travel:60,750 inchesMedia For Which Designed:OilShoff Life:NaChaterial:NaContext Travel:Size Rating:Size Rating:Betterfetive Travel:Size Rating:Float Effective Travel:Size Rating:Size Rating:Pressure Rating:Size Ratin	Terminal Type:	
68.750 inches Current Type: Dc Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travel: S0.750 inches Media For Which Designed: Oil Bethef Life: Na Maid S0.750 inches Gentification Pressure Rating: Oil S0.750 inches Guit for Measure: Oil S0.750 inches Catteriat Guit for Measure: Oil S0.750 inches Catteriat <tr< th=""><th>Stud</th><th></th></tr<>	Stud	
Current Type: Dc Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Metrial: Rubber, buna-n Float Effective Travel: 50.750 inches Media For Which Designed: Oil Shoft Ifie: Na Media For Which Designed: Va Main Float Effective Travel: Na Main Float Messure: - Cannont Float Genes Float Genes Cannont Shoft If If Cannet Na Can	Overall Length:	
De Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travel: S0.750 inches Media For Which Designed: Oil Sn?50 inches Media For Which Designed: Na Diric Na Main Final Na Diric Sn?50 inches Media For Which Designed: Na Diric Sn?50 inches Heilt Heilt Na Diric Sn?50 inches Figure Heilt Heilt <th>68.750 inches</th> <th></th>	68.750 inches	
Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Betrical Connection Controlling Agency: Canon electric Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Heferive Travel: 5.750 inches Metal Point Info Moint Designed: Oil Shafe Tof Which Designed: Na Chit Of Measure: - - Part Infe: Na Chit Of Measure: - - Part Infer: Na Chit Of Heasure: - - Part Infer: Na Chit Of Heasure: - - Part Infer: Na </th <th>Current Type:</th> <th></th>	Current Type:	
Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Presure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, bunan Float FloatCon Pasigned: Sol 750 inches Media For Which Designed: Na Via Dir I of Measure: r r Presser Float Effective Travel: Sol 750 inches Moda For Which Designed: N/a Via Presser Presser Float Effective Travel: Sol 750 inches Mota For Which Designed: N/a Float Self Life: N/a Float Self L	Dc	
Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Flectrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Flective Travel: 59.750 inches Media For Which Designed: Oil Sheff Life: N/a Cit Of Measure: - - Foenilitarization: Yes - demil/mli	Actuation Method:	
Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travel: 59.750 inches Media For Which Designed: Oil Sheff Life: Na Unit Of Measure: - - Demiliatizzation: Yes - demil/mli	Float	
Flectrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 50.750 inches Media For Which Designed: Oil Sheff Life: N/a Entif Measure: Via Float Street: Fig:	Voltage Rating:	
1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 59.750 inches Media For Which Designed: Oil Sheff Life: N/a Electrication: Via Pressure: Via Fig:	Between 10.0 volts and 12.0 volts	
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 59.750 inches Media For Which Designed: Oil Shelf Life: N/a Entit Of Measure: Ford Material: Name Foil Fig:	Electrical Connection Quantity:	
Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 59.750 inches Media For Which Designed: Oil Shelf Life: N/a Lint of Measure: F F F F F F F F F-	1	
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 59.750 inches Media For Which Designed: Oil Sheff Life: N/a Encil Consection For State State: For State: Na Diff Measure: For State: State: For State:	Electrical Connection Controlling Agency:	
Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 59.750 inches Media For Which Designed: Oil Sheff Life: N/a Punitorf Measure: - Pointitarization: Yes - demi/mli	Cannon electric	
Hounting Method:BracketBrasistance In Ohms:5.100 per inch of indicationPressure Rating:Between 0.000 pounds per square inch and 400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:50.750 inchesMedia For Which Designed:OilShelf Life:N/aDint Of Measure:Peniltarization:Yes - demi/mliFig:	Electrical Connection Identifying Number:	
Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 59.750 inches Float Effective Travel: Oil Shelf Life: N/a Littic: Inti of Measure: Demiltarization: Yes - demil/mli Fig:	Part no. 36468	
Resistance In Ohms: 5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 59.750 inches Media For Which Designed: Oil Shelf Life: Ivia Of Measure: Demilitarization: Yes - demil/mli	Mounting Method:	
5.100 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 59.750 inches Media For Which Designed: Oil Shelf Life: N/a Life: Fig:	Bracket	
Pressure Rating:Between 0.000 pounds per square inch and 400.000 pounds per square inchBetween 0.000 pounds per square inch and 400.000 pounds per square inchFloat Material:Float Material:Rubber, buna-nFloat Effective Travel:59.750 inchesMedia For Which Designed:OilShelf Life:N/aInt Of Measure:-Pemilitarization:Yes - demil/mliFig:	Resistance In Ohms:	
Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 59.750 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: - Penilitarization: Yes - demil/mli Fig:	5.100 per inch of indication	
Float Material:Rubber, buna-nFloat Effective Travel:59.750 inchesMedia For Which Designed:OilShelf Life:N/aUnit Of Measure:Demilitarization:Yes - demil/mliFiig:	Pressure Rating:	
Rubber, buna-n Float Effective Travel: 59.750 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Between 0.000 pounds per square inch and 400.000 pounds per square inch	
Float Effective Travel:59.750 inchesMedia For Which Designed:OilShelf Life:N/aUnit Of Measure:Pemilitarization:Yes - demil/mliFig:	Float Material:	
59.750 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Pemilitarization: Yes - demil/mli Fiig:	Rubber, buna-n	
Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Float Effective Travel:	
Oil Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	59.750 inches	
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Media For Which Designed:	
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Filg:	Oil	
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:	
 Demilitarization: Yes - demil/mli Fiig:	N/a	
Yes - demil/mli Fiig:	Unit Of Measure:	
Yes - demil/mli Fiig:		
Fiig:	Demilitarization:	
	Yes - demil/mli	
Т145-b	Fiig:	
	T145-b	