Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-200-2540

Terminal Quantity: 3 Terminal Type: Stud Overall Length: 33.750 inches Current Type: De Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Canone electric Electrical Connection Identifying Number: Part no. 34-68 Mounting Method: S1:00 per inch of indication Pressure Rating: 400:00 pounds per square inch Float Heterial: Pathotes S2:00 per inch of indication Pressure Rating: 400:00 pounds per square inch Float Heteria: Studie: Studie: Valare Shelf Life: Na Dird Identizitation: Na Dird Identizitation: Pathet Identizitation: Na				
Terminal Type: Stud Overal Length: 33.750 inches Current Type: De Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Part no. 3de8a Mounting Method: S100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Herbite: 2000 inches Float Herbite: 2000 inches Float Float Frazel: 2000 inches Float Float Frazel: 2000 inches Marker Shelf Lite: Na Shelf Lite: Na Shelf Lite: Na Shelf Lite: Na Float		/:		
Studi Overal Length: 33.750 inches Current Type: De Attachment Feature Quantity: 2 Attaction Method: Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: 2 Cannon electric Electrical Connection Controlling Agency: Cannon electric Part no. 36488 Mounting Method: Brackel Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 40000 pounds per square inch Float Hereit: Rubber, Dunan Float Floative Travel: 2.3000 inches Materia: Value Shell Line: Na Dut of Measure: Image: Na Shell Line: Na Braitistzation: Na Braitistzation: Na				
Overall Length:33.750 inchesCurrent Type:DeAttachment Feature Quantity:2Actuation Method:FloatVotage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Quantity:2Mounting Method:Part no. 36488Mounting Method:5.100 per inch of indicationPressere Rating:400.000 pounds per square inchFloat Ffective Travel:200.000 pounds per square inchFloat Ffective Travel:200.000 inchesMedia For Which Designed:YaleMadiaDerificial Contextine ContextineFloat Effective Travel:200.000 inchesCommentFloat Effective Travel:200 inchesDerificial:NaFloat Effective Travel:200 inchesDerificia:NaFloat Effective Travel:200 inchesDerificia:NaFloat Effective Travel:200 inchesDerificia:NaStart Effective:NaDerificia:NaDerificia:NaDerificia:NaDerificia:NaDerificia:NaDerificia:NaDerificia:NaDerificia:NaDerificia:Derificia: <th></th> <th></th> <th></th> <th></th>				
3.750 inches Current Type: De Attachment Feature Quantity: 2 Actuation Method: Float Yoltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 par inch of indication Pressure Rating: 400.000 pounds per square inch Float Metrial: Rubber, buna-n Float Effective Travel: 2.030 inches Media For Which Designed: Vater Shif Life: Na Demiliatrization: Na Pressure: Part Part Brancet Float Metrial: Rubber, buna-n Pater Pater </th <th></th> <th></th> <th></th> <th></th>				
Current Type: Dc Attachment Feature Quantity: 2 Actuation Mathod: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Canono electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Stolage Rating: 400.000 pounds per square inch Pressure Rating: 400.000 pounds per square inch Float Hefective Travel: 20.000 inches 20.000 inches Part Inc. Part Method: Stolage Part No. Stolage Part No. <				
De Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Stracket Persure Rating: 400.000 pounds per square inch Float Methol Strabest Mouber, bunan Float Methol Designed: 20.000 inches Made For Which Designed: Vater Stoff Life: Na Desilitarization: Na For Micho Designed: Na Desilitarization:				
Attachment Feature Quantity: 2 Actuation Method: Float Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Flectrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance in Ohms: S100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 23.000 inches Method: S100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 23.000 inches Method: S100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 23.000 inches Method: Stoff Life: Na Comfiliarization: Na Stoff Life:	Current Type:			
2 Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: Electrical Connection Quantity: Cannon electric Electrical Connection Identifying Agency: Cannon electric Electrical Connection Identifying Number: Parto, 38488 Mounting Method: Paracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 23.000 inches Hota Effective Travel: 23.000 inches Metia For Which Designed: Vater Na Metia Messure: To Derilitarization: No				
Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Plactical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 princh of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 23.000 inches Methal: Rubber, buna-n Float Effective Travel: 23.000 inches Methal: Rubber, buna-n Float Effective Travel: 23.000 inches Methal: Rubber, buna-n Float Effective Travel: 23.000 inches Methal: Na Joint Offective Travel: 21.000 inches Methal: Rubber, buna-n Float Effective Travel: 20.000 inches Methal In: Na <th></th> <th>re Quantity:</th> <th></th> <th></th>		re Quantity:		
Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no: 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 23.000 inches Mather Vater Sheft Life: Na Diel Float Schement: Na Diel Float Schement: State I Part no: 300 inches Houter I Part no: 300 inches Houter I Na Diel Float Schement: Na State I Na State I Bracket Pressure Rating: Autor I Part no: 300 inches Houter I Na State I In Uf Measure: - - Part I Na Bracket Na Na Bracket Inter I Na Bracket Part Note Part Note <	2			
Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 23.000 inches Maler For Which Designed: Vatar Shelf Life: Iva Dittor Measure: Iva Float Stract Big:		1:		
Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Effective Travel: 23.000 inches Media For Which Designed: Vater Sheff Life: N/a Ditt Of Measure: ** Demilitarization: No Fig:				
Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 23.000 inches Metal E Of Which Designed: Water Sheft Life: N/a Dint Of Measure: - - Pomilitarization: No Fig:	Voltage Rating:			
1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Paraket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 23.000 inches Media For Which Designed: Water Shelf Life: Na Unit Of Measure: - - Demilitarization: No				
Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 23.000 inches Media For Which Designed: Vater Sheff Life: Na Dint of Measure: Imit of Measure: Imit of Measure: No Fig:	Electrical Connection	tion Quantity:		
Canon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: Canon of indication Pressure Rating: Va0.000 pounds per square inch Va1	1			
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 23.000 inches Media For Which Designed: Vater Shelf Life: Iv/a Dint of Measure: Iv/a Pinitarization: No Fig:	Electrical Conne	tion Controlling Agency:		
Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 23.000 inches Media For Which Designed: Vater Shelf Life: N/a Unit of Measure: Float Effection: No Fig:	Cannon electric			
Mounting Method: Bracket Bracket Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 23.000 inches Method: Prose Material: Na Dir of Measure: - - Ponilitarization: No Fig:	Electrical Conne	tion Identifying Number:		
Bracket Resistance In Ohms: S.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: S.000 inches Media For Which Designed: Vater Shelf Life: N/a Unit Of Measure: Float Of Measure: No Float Signed: Float	Part no. 36468			
Resistance In Ohms: 5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 23.000 inches Media For Which Designed: Yater Shelf Life: N/a Dint Of Measure: Fomiliarization: No Fig:	Mounting Method	:		
5.100 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 23.000 inches Media For Which Designed: Vater Shelf Life: N/a Ditt Of Measure: Fig:	Bracket			
Pressure Rating:400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:23.000 inchesMedia For Which Designed:WaterShelf Life:N/aUnit Of Measure:Pomilitarization:NoFlig:	Resistance In Oh	ms:		
400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 23.000 inches Media For Which Designed: Water Shelf Life: N/a Ditt Of Measure: - Demilitarization: No Fig:	5.100 per inch of i	ndication		
Float Material:Rubber, buna-nFloat Effective Travel:23.000 inchesMedia For Which Designed:WaterShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Pressure Rating:			
Rubber, buna-nFloat Effective Travel:23.000 inchesMedia For Which Designed:WaterShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	400.000 pounds p	er square inch		
Float Effective Travel: 23.000 inches Media For Which Designed: Water Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Float Material:			
23.000 inches Media For Which Designed: Water Shelf Life: N/a Unit Of Measure: No Shelf Life: No Shelf Life: Sh	Rubber, buna-n			
Media For Which Designed: Water Shelf Life: N/a Ditt Of Measure: Demilitarization: No Fig:	Float Effective Tr	avel:		
Water Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	23.000 inches			
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Media For Which	Designed:		
N/a Unit Of Measure: Demilitarization: No Fiig:	Water			
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:			
 Demilitarization: No Fiig:	N/a			
Demilitarization: No Fiig:	Unit Of Measure:			
No Fiig:				
Fiig:	Demilitarization:			
	No			
T145-b	Fiig:			
	T145-b			