Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-200-2553

Terninal Quantity: 3 Terninal Type: Stud Terninal Type: Stud Overall Length: 44.750 inches Current Type: De Attachment Feature Quantity: 2 Attachment Feature Quantity: 3 Attachment Feature Provide Attachment Feature Provide Attachment 3 Attachment F		
Perminal Type: Stud Overal Length: 44.750 inches Current Type: De Attachment Feature Quantity: 2 Attachment Feature Quantity: 1 Polation Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Canon electric Electrical Connection Identifying Number: Part no. 38468 Mounting Method: 10000 per inch of indication Pressure Rating: 10000 pounds per square inch Rouber, buna-n Pater Effective Travel: 10000 pounds per square inch Float Metrial: Rubber, buna-n Float Effective Travel: 34,000 inches Meader br Which Designed: Na Material: Na Material: Na Material: Na Material: Na Material: </th <th></th> <th>rminal Quantity:</th>		rminal Quantity:
Slud Voral Length: 4.750 inches 4.750 inches Current Type: Current Type: Common Sector		
Overall Length:44.750 inchesCurrent Type:DeAttachment Feature Quantity:2Actuation Method:FloatVolag Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricPart no. 36468Mounting Method:10000 per Inch of IndicationPressure Rating:100.000 per unch of IndicationPressure Rating:200.000 pounds per square inchFloat Friedrice Travel:34.000 inchesHouting Method:10.000 per unch of IndicationPressure Rating:200.000 pounds per square inchFloat Effective Travel:34.000 inchesModia For Which Designed:CitModia For Mich Designed:NaDirifitrizzation:NaFloat Iffective:NaFloat Iffective:NaFloat Iffective:NaFloat Iffective:NaFloat Iffective:NaPomilitrizzation:NaFloat Iffective:NaPomilitrizzation:NaFloatFloatFloatPomilitrizzation:NaFloatFloatFloatFloatFloatFloatFloatFloatFloatFloat <t< th=""><th></th><th></th></t<>		
44.750 incless Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Viatage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10.0000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Metrial: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Shif Life: Iva Chif Measure: Imiliarization: No Shif Life: Iva Electrical Colu Shif Life: Iva Electrical Colu Shif Life: Iva Electrical Colu		
Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Methol Stober, bunan Float Fleative Travel: Aubour, bunan Float Hefective Travel: Aubour, bunan		
Dc Atachment Feature Quantity: 2 Actation Method: Float Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10.000 pounds per square inch Float Metarial: Nubber, buna-n Float Metarial: Rubber, buna-n Float Floative Tavoel: Quotons be Quotons be Mouting MethoD: Staterial: Nubber, buna-n Float Hereine: Quotons be Quotons be Quotons be Part In: Na Quotons be Guit Staterial: Na Dill Staterial: Na Dill Staterial: Na Stateria: Na Na Na Stateria: Na Stateria: Na Na Na Stateria: <		
Attachment Feature Quantity: 2 Actuation Method: Float Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Ruber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Sheff Life: Na Carlielitizzion: Na Strip Company		
2 Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: Centrol Quantity: Cannon electric Cannon electric Cannon electric Electrical Connection Identifying Number: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bratket Resistance In Ohms: 10.000 per inch of indication Pressure Rating: 10.000 per unch of Indication Pressure Rating: 10.000 pounds per square inch Float Metrial: Rubber, buna-n Float Metrial: Rubber, buna-n Float Effective Travel: 34.000 inches Metria For Which Designed: 04.000 inches Metria For Which Designed: 05.000 inches Metria For Which Designed: 05.0000 inches Metria For Which Designed: 05.0000 inches Metria For Which Designed: 05.00000 inches Metria For Which Designed: 05.00000000000000000000000000000000000		
Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Meterial: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Sheft Ite: Na Material: Rubber, buna-n Float Meterial: Na Sheft Ite: Na Dil Float States Float States Media For Which Designed: Na Sheft Ite: Na Float States Float States Sheft Ite: Na		tachment Feature Quantity:
Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Affective Travel: 34.000 inches Heat For Which Designed: Oil Sheft Life: Na Unt Of Measure: - Part no: Na Dirig:		
Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no: 36468 Mounting Method: Bracket Resistance In Ohms: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Affective Travel: 34.000 inches Media For Which Designed: Oil Sheft Itie: Na Unit Of Measure: - Part Inc. Na Sheft Itie: Na Duit Of Measure: - Penilliarization: No Fig:		
Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Sheff Life: N/a Dit Of Measure: - - Penilitarization: No Fig:		
Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10.000 port inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Sheff Life: N/a Ditt Of Measure:		
1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Shelf Life: N/a Lint Of Measure:		
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10:00 per inch of indication Pressure Rating: 400:000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 34:000 inches Media For Which Designed: Oil Sheff Life: N/a Ditt Of Measure: · Part Of Material: Noil Biff Life: N/a Diff Life: N/a Find To Measure: · Part Of Measure: · Part Differiation: No Fig:	Ele	ectrical Connection Quantity:
Canon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Shelf Life: N/a Lift of Measure: Demilitarization: No	1	
Electrical Connection Identifying Number: Part no. 36468 Mouning Method: Bracket Brasistance In Ohms: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Sheff Life: Na Did Masure: - maint of Measure: Na Ford Illitarization: No Fig:	Ele	ectrical Connection Controlling Agency:
Part no. 36468Mounting Method:BracketResistance In Ohms:10.000 per inch of indicationPressure Rating:400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:34.000 inchesMedia For Which Designed:OilShelf Life:N/aDint of Measure:Pemilitarization:NoFig:	Ca	nnon electric
Mounting Method:BracketBrastance In Ohms:Resistance In Ohms:10:000 per inch of indicationPressure Rating:400:000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:34:000 inchesMedia For Which Designed:OilShelf Life:N/aDint of Measure:Pemilitarization:NoFig:	Ele	ectrical Connection Identifying Number:
Bracket Resistance In Ohms: I Resistance In Ohms: I Root per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: S4.000 inches Gudia For Which Designed: Oil Shelf Life: N/a Littic: I Ro I Fig: I I I I I I I I.	Pa	rt no. 36468
Resistance In Ohms: 10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Shelf Life: Iva Punitor of Measure: Iva For Michasure: Formiliarization: No Fig:	Мо	ounting Method:
10.000 per inch of indication Pressure Rating: 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Shelf Life: N/a Dit Of Measure: Fig:	Bra	acket
Pressure Rating:400.000 pounds per square inch400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:34.000 inchesMedia For Which Designed:OilShelf Life:N/aUnit Of Measure:-Penilitarization:NoFig:	Re	esistance In Ohms:
400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	10	.000 per inch of indication
Float Material:Rubber, buna-nFloat Effective Travel:34.000 inchesMedia For Which Designed:OilShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Pr	essure Rating:
Rubber, buna-n Float Effective Travel: 34.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	40	0.000 pounds per square inch
Float Effective Travel: 34.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Flo	oat Material:
34.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Penilitarization: No Fig:	Ru	ibber, buna-n
Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Flo	pat Effective Travel:
Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	34	.000 inches
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Me	edia For Which Designed:
N/a Unit Of Measure: Demilitarization: No Fiig:	Oil	
Unit Of Measure: Demilitarization: No Fiig:	Sh	elf Life:
 Demilitarization: No Fiig:	N/a	a
Demilitarization: No Fiig:	Un	nit Of Measure:
No Fiig:		
Fiig:	De	emilitarization:
	No	
T145-b	Fii	g:
	T1	45-b