## NSN 6680-01-201-8271

**Media For Which Designed:** 

**Inlet Connection Type:** 

**End Application:** 

**Integral Relief Valve:** 

Air

Threaded

F-16 aircraft

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-201-8271

Not included
Accessory Components And Quantity:
Pointer flag, 1
Meter Type:
Float
Design Type:
Case
Unit Type:
Mounted
Scale Quantity:
1
Construction:
Inclosed w/sight window
Outlet Connection Type:
Threaded
Scale Marking:
Cc air per min
Scale Type:
Direct capacity reading
Float Quantity:
1
Tube Material:
Plastic
Mounting Method:
Flush panel or surface panel
Carrying Handle:
Not included
Dial Scale Marking Range:
+50.0/+500.0
Outlet Connection Size:
0.125 in. Npt
Base:
Not included
Float Type:
Guided

## NSN 6680-01-201-8271

Flow Rate Indicating Meter - Page 2 of 2



Float Material:
Any acceptable
Guide Type:
Any acceptable
Integral Heat Source:
Not included
Maximum Working Pressure:
100.0 pounds per square inch
Inlet Connection Size:
0.125 in. Npt
Metering Tube Quantity:
1
Dial Scale Smallest Increment:
10cc
Dial Scale Reference Pointer:
Included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Vertical
Outlet Connection Position For Which Designed:
Vertical
Alarm Signal:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t