NSN 6680-01-203-7744

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-203-7744

Media For Which Designed:
Air
Inlet Connection Type:
Any acceptable
End Application:
Howell labs inc air control panel, model 2800
Integral Relief Valve:
Not included
Meter Type:
Float
Design Type:
Case
Unit Type:
Mounted
Scale Quantity:
1
Construction:
Inclosed w/sight window
Outlet Connection Type:
Any acceptable
Scale Marking:
Standard cu ft per min
Scale Type:
Direct capacity reading
Float Quantity:
1
Tube Material:
Glass
Mounting Method:
Flush panel
Dial Scale Marking Range:
+0.0/+10.0
Float Type:
Free
Float Material:
Steel, stainless
Integral Heat Source:
Not included
Maximum Working Pressure:
50.0 pounds per square inch
Metering Tube Quantity:

NSN 6680-01-203-7744

Flow Rate Indicating Meter - Page 2 of 2



Spinning Float:
Not included
Integral Pulsation Dampener:
Included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Connection size 0.875 in. Smooth bore o-ring fit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t