Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-212-6458

Overall Length:

4.030 inches

Media For Which Designed:

Air

Inlet Connection Type:

Threaded

End Application:

Low pressure air-dehydrators

Integral Relief Valve:

Not included

Meter Type:

Float

Design Type:

Case

Unit Type:

Mounted

0.....

Scale Quantity:

1

Construction:

Inclosed w/sight window

Outlet Connection Type:

Threaded

Scale Marking:

Standard cubic feet per minute

Scale Type:

Direct capacity reading

Float Quantity:

1

Tube Material:

Glass

Mounting Method:

Flush panel

Carrying Handle:

Not included

Dial Scale Marking Range:

+10.0 to 100.0

Outlet Connection Size:

0.750 in. Od

Base:

Not included

Float Type:

Free

NSN 6680-01-212-6458

Flow Rate Indicating Meter - Page 2 of 2



Float Material: Glass **Integral Heat Source:** Not included Maximum Working Pressure: 150.0 pounds per square inch Inlet Connection Size: 0.750 in. Od Metering Tube Quantity: 1 **Dial Scale Smallest Increment:** 10 standard cubic feet per minute **Dial Scale Reference Pointer:** Not included **Spinning Float:** Not included **Integral Pulsation Dampener:** Not included Inlet Connection Position For Which Designed: Horizontal Inlet Connection Device Type: Stationary **Outlet Connection Position For Which Designed:** Horizontal **Outlet Connection Device Type:** Stationary Alarm Signal: Not included Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: T134-t