NSN 6680-01-213-1740

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-213-1740 **Inlet Connection Type:** Threaded **Design Type:** Case **Scale Quantity:** 2 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Dial Scale Marking Range:** +60.0 to 400.0 **Outlet Connection Size:** 0.750 in. Unc Float Type: Free Float Material: Aluminum **Maximum Working Pressure:** 175.0 pounds per square inch **Inlet Connection Size:** 0.750 in. Unc **Metering Tube Quantity: Dial Scale Reference Pointer:** Not included **Spinning Float:** Not included **Integral Pulsation Dampener:** Not included **Inlet Connection Position For Which Designed:** Horizontal **Inlet Connection Device Type:**

Stationary

Outlet Connection Position For Which Designed:

Horizontal

NSN 6680-01-213-1740

Fiig: T134-t

Flow Rate Indicating Meter - Page 2 of 2



Outlet Connection Device Type:
Stationary
Special Features:
Bottom float, 316 stainless steel; right scale range, 380 to 2200 pounds per hour
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No