NSN 6680-01-225-4472

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-225-4472 **Overall Length:** 7.156 inches Media For Which Designed: Liquid **Inlet Connection Type:** Threaded **End Application:** Poseidon **Integral Relief Valve:** Not included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 2 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading Float Quantity: **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +2.0 to 30.0

Outlet Connection Size:
0.750 in. Npt
Base:
Not included
Float Type:
Free
Float Material:
Aluminum

NSN 6680-01-225-4472

Flow Rate Indicating Meter - Page 2 of 2



Integral Heat Source:
Not included
Maximum Working Pressure:
3000.0 pounds per square inch
Inlet Connection Size:
0.750 in. Npt
Dial Scale Smallest Increment:
0.2 gpm
Dial Scale Reference Pointer:
Not included
Spinning Float:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t