## NSN 6680-01-226-1232

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-226-1232 **Overall Length:** 7.156 inches Media For Which Designed: 0il **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Design Type:** Glass **Unit Type:** Mounted **Scale Quantity: Outlet Connection Type:** Threaded **Scale Marking:** Gal per min Scale Type: Direct capacity reading Float Quantity: 1 **Mounting Method:** Direct line **Dial Scale Marking Range:** +2.0 to 30.0 **Outlet Connection Size:** 0.750 in. Npt Float Type: Guided **Guide Type:** Solid rod **Integral Heat Source:** Not included **Maximum Working Pressure:** 3000.0 pounds per square inch **Inlet Connection Size:** 0.750 in. Npt **Dial Scale Reference Pointer:** Not included **Spinning Float:** 

Not included

## NSN 6680-01-226-1232

Flow Rate Indicating Meter - Page 2 of 2



Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t