Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-263-4067

	overall Length:
7	.750 inches
N	ledia For Which Designed:
L	iquid
lr	nlet Connection Type:
Т	hreaded
lr	ntegral Relief Valve:
N	lot included
N	leter Type:
F	loat
D	esign Type:
С	ase
U	Init Type:
N	lounted
S	cale Quantity:
1	
С	construction:
S	ide plate
0	outlet Connection Type:
Т	hreaded
S	cale Marking:
G	Spm
S	cale Type:
D	irect capacity reading
F	loat Quantity:
1	
Т	ube Material:
G	ilass
N	Iounting Method:
D	irect line
С	arrying Handle:
N	lot included
D	ial Scale Marking Range:
+	0.0/+0.5
0	Outlet Connection Size:
0	.750 in. Npt
В	ase:
N	lot included
F	loat Type:
F	ree
F	loat Material:
_	teel, stainless

Flow Rate Indicating Meter - Page 2 of 2



Integral Heat Source: Not included Maximum Working Pressure: 200.0 pounds per square inch Inlet Connection Size: 0.500 in. Npt Metering Tube Quantity: 1 **Dial Scale Reference Pointer:** Not included **Spinning Float:** Not included **Integral Pulsation Dampener:** Not included Alarm Signal: Not included Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T134-t