Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-280-8886

| Terninal Quantity: 6 Ferninal Type: Stud Overall Length: 76.375 inches Current Type: Dc Attachment Feature Quantity: 2 Attachment Feature Quantity: 2 Attachment Feature Quantity: 2 Hoat Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Quantity: 2 Electrical Connection Quantity: 2 Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Brackel Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travel: 7.000 inches Media For Which Designed: Vater Sheff Life: Na Demiliarization: No Fig: Fig: Fig: | |
|--|---|
| Struct Struct Overall Length: 78.375 inches Current Type: De De Attachment Feature Quantity: 2 Attachment Feature Quantity: Pate Attachment Job Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Monting Method: Stocket Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Batterial: Ruber, Jounan Hott Metrial: Ruber, Jounan Float Effective Travel: 7.000 inches Material: Nator Stall Line: Nator Nator Stall Line: Nator Stall Line: Nator Stall Line: | Terminal Quantity: |
| Studi Vorall Length: 76.376 Inches Current Type: Current Type: Bat Attachment Feature Quantity: 2 Attacht Method: Float Outage Rating: Batween 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Quantity: 2 Electrical Connection Quantity: 2 Canone alectric Canone alectric Batton: Scatton Method: Bracket Mounty Method: Bracket Resistance In Ohms: Scattop Electrical Controlling Agency: Scattop Electrical Controlling Agency: Scattop Electrical Controlling Agency: Bracket Bracket Bracket Bracket Bracket Resistance In Ohms: Scattop Electrical Travel: Rober Duolop punds per square lond and 400.000 pounds per square lond Flat Effective Travel: Toutoto Resignet: | |
| Nevral Length:76.375 inchesCurrent Type:DeAttachment Feature Quantity:2Attaction Method:FloatVolage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:2Electrical Connection Quantity:2Monting Method:Float HouseMounting Method:Part no. 36468Mounting Method:Betore Rating:Betore Rating:Point Betore:Point Betore: <th></th> | |
| 78.375 inclust Current Type: De Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 38468 Mounting Method: Bracket Resistance In Ohms: 6.200 per inch of indication Presure Rating: Between 0.0000 pounds per square inch and 400.000 pounds per square inch Float Metrict: Rubber, buna-n Hoat Effective Travel: Rubber, buna-n Float Effective Travel: Rubber, buna-n Hoat Effective Travel: Ruba Hoat Effective Travel | |
| Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Part no. 36468 Part Set Table Part Set Table | |
| Dc Atachment Feature Quantity: 2 Actuation Method: Float Float Polage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Eracket Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travei: 7.000 inches Float Effective Travei: 7.000 inches Houter Eracket: 7.000 inches Float Effective Travei: 7.000 inches Metaer Part Iffective Travei: 7.000 inches Float Effective Travei: 7.000 inches Part Iffective Travei: 7.000 inches Part Iffective Travei: < | |
| Atachment Feature Quantity: 2 Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Batween 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travel: 7.000 inches Float Effective Travel: 7.000 inches Method: Part Infer: Nubber, buna-n Float Effective Travel: 7.000 inches Bellet Life: Na Part Infer: Na Child Measure: Na Danilization: Na State S | |
| 2 Acuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: Electrical Connection Quantity: Cannon electric Electrical Connection Identifying Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Part no. 36468 Part no | Dc |
| Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Parcekt Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Meterial: Rubber, buna-n Float Fleative Travel: 7.000 inches Meterial: Rubber, buna-n Float Meterial: 7.000 inches Meterial: 7.000 inches Meterial: Na Shaft Infi: Na Shaft Infi: < | Attachment Feature Quantity: |
| Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Paracket Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 7.000 inches Material: Water Sheff Life: Na Uit Of Measure: - Panel No Fig: | 2 |
| Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 6.200 per linch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 7.000 inches Method: Vater Dit Of Measure: .va Dit Of Measure: .va Fig: | Actuation Method: |
| Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 6.200 per inch of indication Presure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 7.0.000 inches Molt For Which Designed: Valer Sheff Life: N/a Lint Of Measure: - Fomiliarization: No Fig: | |
| Electrical Connection Quantity: 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Vater Sheff Life: N/a Lint Of Measure: - - Pimilitarization: No Fig: | Voltage Rating: |
| 2 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Paraket Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Retween 0.000 pounds per square inch and 400.000 pounds per square inch for Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Water Sheff Life: Na Sheff Life: Na Dit Of Measure: Tomiliatization: No | Between 10.0 volts and 12.0 volts |
| Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 6200 pr inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Vater Sheff Life: N/a Chit Of Measure: Image: No Fig: | Electrical Connection Quantity: |
| Canon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Resistance In Ohms: Cacoo per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: Toolo inches Media For Which Designed: Vater Sheff Life: N/a Lif | 2 |
| Flectrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Bracket Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Vater Shelf Life: Na Ent of Measure: r Point Interaction: r for for forig | Electrical Connection Controlling Agency: |
| Part no. 36468 Mounting Method: Bracket Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Vater Shelf Life: N/a Entife Masure: - - Penilitarization: No Fig: | Cannon electric |
| Mounting Method:BracketBrasistance In Ohms:6.200 per inch of indicationPressure Rating:Between 0.000 pounds per square inch and 400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:70.000 inchesMedia For Which Designed:VaterShelf Life:NaDemiltarization:-Fon:Final Filte: <th>Electrical Connection Identifying Number:</th> | Electrical Connection Identifying Number: |
| Bracket Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Vater Shelf Life: N/a Lift Of Measure: Demiltarization: No Fig: | Part no. 36468 |
| Resistance In Ohms: 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Vater Shelf Life: N/a Dint Of Measure: Fomilitarization: No Fig: | Mounting Method: |
| 6.200 per inch of indication Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Float Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Vater Shelf Life: N/a Unit Of Measure: Sheli Life: No Fig: | Bracket |
| Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Vater Shelf Life: N/a Dint Of Measure: Formilitarization: No Fig: | Resistance In Ohms: |
| Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Water Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig: | 6.200 per inch of indication |
| Float Material:Rubber, buna-nFloat Effective Travel:70.000 inchesMedia For Which Designed:WaterShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | Pressure Rating: |
| Rubber, buna-n Float Effective Travel: 70.000 inches Media For Which Designed: Water Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Between 0.000 pounds per square inch and 400.000 pounds per square inch |
| Float Effective Travel:70.000 inchesMedia For Which Designed:WaterShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | Float Material: |
| 70.000 inchesMedia For Which Designed:WaterShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | Rubber, buna-n |
| Media For Which Designed: Water Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Float Effective Travel: |
| Water Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 70.000 inches |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Media For Which Designed: |
| N/a Unit Of Measure: Demilitarization: No Fiig: | Water |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: |
| Demilitarization: No Fiig: | N/a |
| Demilitarization: No Fiig: | Unit Of Measure: |
| No Fiig: | |
| Fiig: | Demilitarization: |
| | No |
| T145-b | Fiig: |
| | T145-b |
| | |