Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-281-9656

Terminal Quantity: 3 Ferminal Type: Stud Overall Length: 119.750 inches Current Type: Dc Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Electrical Connection Quantity: 1 Electrical Connection Quantity: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material:
Terminal Type: Stud Overall Length: 119.750 inches Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: 1 Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch.
Stud Overall Length: 119.750 inches Current Type: Dc Attachment Feature Quantity: 2 Attachment Feature Quantity: 2 Attacion Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Overall Length:119.750 inchesCurrent Type:DcDcAttachment Feature Quantity:2Actuation Method:FloatVoltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1Electrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketPressure Rating:Between 0.000 pounds per square inch and 400.000 pounds per square inch
119.750 inches Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Dc Attachment Feature Quantity: 2 Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: Cannon electric Electrical Connection Identifying Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Attachment Feature Quantity: 2 Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch
Between 0.000 pounds per square inch and 400.000 pounds per square inch
Float Material:
Rubber, buna-n
Float Effective Travel:
109.000 inches
Media For Which Designed:
Oil
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т145-b