Liquid Quantity Transmitter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6680-01-285-8307

Terminal Guantity: 3 Terminal Type: Stud Overall Length: 94.750 inches Current Type: Do Attachment Feature Quantity: 2 Attachment Feature Quantity: 2 Attachment Feature Quantity: 2 Attachment Feature Quantity: 2 Attachment Feature Quantity: 2 Attachment Feature Quantity: 1 Electrical Connection Quantity: 1 Electrical Connection Quantity: 1 Electrical Connection Quantity: 1 Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36:468 Mouning Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travel: 84:000 inches Media For Which Designed: Oil Shell If: Na Unit Of Measure: Penilitarization: No Flig: T145-b	
Ferninal Type: Stud 94.750 inches 94.750 inches Current Type: De Attachment Feature Quantity: 2 Attachment Feature Quantity: Polation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travel: Rubber, buna-n Float Effective Travel: Buber (Dui nches) Modia For Which Designed: Na Uri of Measure: Na Denlitarization: Na Burling Liter	Terminal Quantity:
Stud Overall Length: 94.750 inches Current Type: De Attachment Feature Quantity: 2 Actuation Method: Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Station Method: Connon electric Electrical Connection Controlling Agency: Cannon electric Parto: Parto: Parto: Parto: Stacker Possure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Heferciter Tavel: Stacker Parto: Stacker Parto: Stacker Parto: Station Micho Heasure: Station Micho Heasure: Station Micho Heasure: Station Micho Heasure: Otil Station Micho Heasure: Otil Station Micho Heasure: Station Micho Heasure: Stati III:<	
Overall Length: 94.750 inches Current Type: De Attachment Feature Quantity: 2 Actuation Method: Float Vortage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 30408 Mouning Method: Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Hereine: Aubder, bunan Float Hereine: Aubder, bunan Float Hereine: Aubder (Ditho Designed: Ori Stoff Life: Na Chif Measure: Tree Peniliarization: No Pig:	
94.750 Inches Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Plettrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Retween 0.000 pounds per square inch and 400.000 pounds per square inch Float Hefetive Travel: 84.000 inches Hout for Which Designed: Oil Sheft Life: Na Chif Measure: Canon chif Measure: Canon chif Measure: Canon chif Measure: Canon chif Measure: Rubber, buna-n Float Effective Travel:	
Current Type: Dc Attachment Feature Quantity: 2 Actuation Method: Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Quantity: Cannon electric Electrical Connection Identifying Agency: Cannon electric Part no. 36468 Mouting Method: Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Hier Rubber, buna-n Float Effective Travel: 84.000 inches Media For Which Designed: Oil Shore Name Int If Measure: Na Muit Of Measure: Na Shore Name Int Interset Na Int Interset Na Int Interset Na Int Interset Int Interset Int Interset Int Interse Int Interset	
Dc Attachment Feature Quantity: 2 Actuation Method: Float Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Moutring Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travel: 84.000 inches Media For Which Designed: Oil State Inter: Na Moil Tor Mouting Methol: Na Moto Inches Media For Which Designed: Na Na Na Picelitier: Na Fig:	
Attachment Feature Quantity: 2 Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Float Peterical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Effective Travel: Rubber, buna-n Float Effective Travel: Bound inches Media For Which Designed: Oil Stell Life: Na Catter Composition Comp	
2 Actuation Method: Float Float Vottage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Part no. 36468 Mounting Method: Bracket Parsure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Affective Travel: 84.000 inches Meta For Which Designed: Ma Bracket Ma Moint Seisen: Tr Part Ini: Na Ma Part Ini: Na Part Ini: Na Part Ini: Na Part Ini: Part Ini: Part Ini: Part Part Part Part Part Part Part Part	
Actuation Method: Float Voltage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Float Effective Travel: 84.000 inches Media For Which Designed: Na Via Piot Effective: Na Piot Of Measure: - Piot Iffe: Na Piot Of Measure: - Pionilitarization: No Fig:	
Float Votage Rating: Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float FloatCrive Travel: 84.000 inches Media For Which Designed: Oil Sheff Life: Na Procesure: To Point Material: Rubber, buna-n Float Effective Travel: Boling Boling Boling Divid Float Effective Travel: Na Prove Na Prove Prove Prove Boling Boling Boling Boling Prove	
Voltage Rating:Between 10.0 volts and 12.0 voltsElectrical Connection Quantity:1fElectrical Connection Controlling Agency:Cannon electricElectrical Connection Identifying Number:Part no. 36468Mounting Method:BracketPressure Rating:Between 0.000 pounds per square inch and 400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:84.000 inchesMedia For Which Designed:OilShelf Life:NaUnit of Measure:INaFig:No	
Between 10.0 volts and 12.0 volts Electrical Connection Quantity: 1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 84.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Bettween 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 84.000 inches Dil Sheff Life: N/a Dint of Measure: Imit of Measure: Imit of Measure: No Fig:	
1 Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 84.000 inches Media For Which Designed: Oil Shelf Life: N/a Entor of Measure: Image: No Fig:	
Electrical Connection Controlling Agency: Cannon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 84.000 inches Media For Which Designed: Oil Shelf Life: N/a Dint of Measure: - Pomilitarization: No Fig:	
Canon electric Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 84.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Electrical Connection Identifying Number: Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: A000 inches Media For Which Designed: Oil Shelf Life: Ivid Of Measure: Dinitorization: No Fig:	
Part no. 36468 Mounting Method: Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 84.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Mounting Method:BracketBressure Rating:Between 0.000 pounds per square inch and 400.000 pounds per square inchFloat Material:Rubber, buna-nFloat Effective Travel:84.000 inchesMedia For Which Designed:OilShelf Life:N/aUnit Of Measure:Poillitarization:NoFig:	
Bracket Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: Rubber, buna-n Float Effective Travel: 84.000 inches Media For Which Designed: 0il Shelf Life: N/a Dit Of Measure: Demilitrization: No Flig:	
Pressure Rating: Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Rubber, buna-n B4.000 inches Media For Which Designed: Oil Sheff Life: N/a Dint Of Measure: - Penilitarization: No Fig:	
Between 0.000 pounds per square inch and 400.000 pounds per square inch Float Material: Rubber, buna-n Float Effective Travel: 84.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Float Material:Rubber, buna-nFloat Effective Travel:84.000 inchesMedia For Which Designed:OilShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:	
Rubber, buna-n Float Effective Travel: 84.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Float Effective Travel: 84.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No	
84.000 inches Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: No Shelf Life: No Shelf Life: Shel	
Media For Which Designed: Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Oil Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
T145-b	
	Т145-b