NSN 6680-01-300-4834

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-300-4834 **Overall Length:** 8.375 inches Media For Which Designed: Gas **Inlet Connection Type:** Threaded **Integral Relief Valve:** Not included **Indicator Type:** Ball float **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Cubic centimeters per minute Scale Type: Direct capacity reading Float Quantity: **Tube Material:** Glass **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.0/+54000.0 **Outlet Connection Size:** 0.250 in. Npt Base: Not included Float Type: Free

NSN 6680-01-300-4834

Flow Rate Indicating Meter - Page 2 of 2



| Integral Heat Source: |
|--|
| Not included |
| Maximum Working Pressure: |
| 300.0 pounds per square inch |
| Inlet Connection Size: |
| 0.250 in. Npt |
| Metering Tube Quantity: |
| 1 |
| Dial Scale Reference Pointer: |
| Not included |
| Spinning Float: |
| Not included |
| Integral Pulsation Dampener: |
| Not included |
| Inlet Connection Position For Which Designed: |
| Horizontal |
| Inlet Connection Device Type: |
| Stationary |
| Outlet Connection Position For Which Designed: |
| Horizontal |
| Outlet Connection Device Type: |
| Stationary |
| Alarm Signal: |
| Not included |
| Special Features: |
| Float no. Bt-8 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T134-t |