Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-308-0016

Overall	Length:
7.500 in	ches
Media F	or Which Designed:
Water	
Inlet Co	nnection Type:
Threade	d
End Ap	plication:
Mk 92, r	nod 6, interim support
Integral	Relief Valve:
Not inclu	ıded
Meter T	ype:
Pointer of	connected to vane
Design	Туре:
Case	
Unit Typ	be:
Mounted	i de la constante de
Scale Q	uantity:
1	
Constru	iction:
Inclosed	w/sight window
Outlet C	Connection Type:
Threade	d
Scale M	arking:
Gpm	
Scale T	ype:
Direct ca	apacity reading
Mountir	ng Method:
Direct lir	ne
Carrying	g Handle:
Not inclu	ıded
Dial Sca	ale Marking Range:
+0.0/+5.	0
Base:	
Included	
Integral	Heat Source:
Not inclu	ıded
Inlet Co	nnection Size:
0.500 in	. Ips
Maximu	m Water Capacity In Gallons Per Minute:
5.0	
Dial Sca	ale Reference Pointer:
Included	

NSN 6680-01-308-0016

Flow Rate Indicating Meter - Page 2 of 2



Integral Pulsation Dampener: Not included Inlet Connection Position For Which Designed: Vertical **Outlet Connection Position For Which Designed:** Vertical Alarm Signal: Not included Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T134-t