NSN 6680-01-322-7216



Flow Rate Indicating Meter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6680-01-322-7216 **Overall Length:** 8.125 inches Media For Which Designed: Liquid **Inlet Connection Type:** Threaded **End Application:** 4920-01-245-5139 test kit flow measurement f-15a/b/c/d acft **Integral Relief Valve:** Not included **Meter Type:** Piston/spring **Design Type:** Case **Unit Type:** Mounted or portable **Scale Quantity:** 1 **Construction:** Armored **Outlet Connection Type:** Threaded Scale Marking: Gpm Scale Type: Direct capacity reading **Mounting Method:** Any acceptable **Carrying Handle:** Not included **Dial Scale Marking Range:** +5.0/+30.0 **Outlet Connection Size:** 0.500 in. Npt Base: Not included **Integral Heat Source:** Not included **Maximum Working Pressure:** 300.0 pounds per square inch

Inlet Connection Size:

0.500 in. Npt

NSN 6680-01-322-7216

Flow Rate Indicating Meter - Page 2 of 2



Dial Scale Smallest Increment:
5 gallons
Dial Scale Reference Pointer:
ncluded
ntegral Pulsation Dampener:
Not included
nlet Connection Position For Which Designed:
Horizontal
nlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Piston material aluminum; internalmaterials stainless steel; seal material buna n; max flow 12 gpm; flow direction left to right; inlet port
position lower side of meter
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
Γ134-t