

View Online at <https://aerobasegroup.com/nsn/6680-01-383-7933>

**Length:**

17.000 inches

**Ac Voltage Rating:**

115.0 volts or 230.0 volts

**Frequency Rating:**

60.0 hertz

**Major Components:**

Front panel assembly which consists of 16 button keypad and 2 line x 16 character display, high speed motor, speed feedback sensor sys, 1000 watt dc power supply

**Depth:**

18.000 inches

**Accessory Component Quantity:**

8

**Electrical Power Source Relationship:**

Operating

**Inclosure Feature:**

Multiple item w/carrying case

**Test Type For Which Designed:**

Tachometer tester for all known tachometers used by the u.S.A.F.

**Operating Test Capability:**

Revolutions per minute in ranges of 0-100, 0-500, 0-1000, 0-5000, 0-10000, 0-20000, 0-30000, and 0-40000 rpm

**Phase:**

Single

**Special Features:**

Rotational speed 55 to 40, 000 rpm both cw and ccw; linear rate variable; accuracy +/- 0.005 percent of reading +/- one digit; torque 40 in-oz at 5000 rpm; installation and unpacking should be performed by pmel

**Functional Description:**

Tachometer calibrator will provide pmels with an improved capability to calibrate all known types of tachometers used by the usaf

**Height:**

19.000 inches

**Relationship To Similar Equipment:**

REPL-AC-ESN-SN66

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T228-a