

View Online at <https://aerobasegroup.com/nsn/6680-01-383-7933>

Length:

17.000 inches

Ac Voltage Rating:

115.0 volts or 230.0 volts

Frequency Rating:

60.0 hertz

Major Components:

Front panel assembly which consists of 16 button keypad and 2 line x 16 character display, high speed motor, speed feedback sensor sys, 1000 watt dc power supply

Depth:

18.000 inches

Accessory Component Quantity:

8

Electrical Power Source Relationship:

Operating

Inclosure Feature:

Multiple item w/carrying case

Test Type For Which Designed:

Tachometer tester for all known tachometers used by the u.S.A.F.

Operating Test Capability:

Revolutions per minute in ranges of 0-100, 0-500, 0-1000, 0-5000, 0-10000, 0-20000, 0-30000, and 0-40000 rpm

Phase:

Single

Special Features:

Rotational speed 55 to 40, 000 rpm both cw and ccw; linear rate variable; accuracy +/- 0.005 percent of reading +/- one digit; torque 40 in-oz at 5000 rpm; installation and unpacking should be performed by pmel

Functional Description:

Tachometer calibrator will provide pmels with an improved capability to calibrate all known types of tachometers used by the usaf

Height:

19.000 inches

Relationship To Similar Equipment:

REPL-AC-ESN-SN66

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T228-a