

View Online at <https://aerobasegroup.com/nsn/6680-01-449-9921>

**Width:**

4.000 inches

**Thickness:**

1.400 inches

**Length:**

7.500 inches

**Dc Voltage Rating:**

9.0 volts

**Major Components:**

2 adapter cables

**Electrical Power Source Relationship:**

Self-contained

**Internal Battery Accommodation:**

Included

**Material And Location:**

Plastic, phenolic carrying case

**Inclosure Feature:**

Single item w/carrying case

**Test Type For Which Designed:**

Simulate rate of flow transmitter output, 8tj124 series

**Operating Test Capability:**

Five test point selections (hi range 1350, 6750, 13500, 20250, and 27000pph) (lo range 600, 3000, 6000, 9000, and 12000 pph)

**Special Features:**

Y9 volt alkaline battery, 2 green leds indicate start and stop pulse, 1 red for battery lo voltage, operating -4 to 120 degrees f., designed for flightline use, meets protection requirements of class ii per iec 348, ansi c39.5 and ul1244

**Functional Description:**

Simulates the 8tj124 series turbine flow transmitter output, used for on line troubleshooting

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T228-a