NSN 6680-01-481-7614

Overall Length: 40.874 inches

Not included

Inlet Connection Type:

Flow Rate Indicating Meter - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/6680-01-481-7614



Flange **End Application:** Nimitz class cvn **Integral Relief Valve:** Included **Meter Type:** Float **Design Type:** Case **Unit Type:** Mounted **Scale Quantity: Construction:** Inclosed w/sight window **Outlet Connection Type:** Flange Float Quantity: 1 **Mounting Method:** Direct line **Carrying Handle:** Not included **Unit Location:** Any acceptable **Dial Scale Marking Range:** +0.0/+2000.0 Base: Not included Float Type: Guided Float Material: Steel, stainless **Guide Type:** Solid rod **Integral Heat Source:** Not included **Dial Scale Reference Pointer:**

NSN 6680-01-481-7614Flow Rate Indicating Meter - Page 2 of 2



| Spinning Float: |
|--|
| Not included |
| ntegral Pulsation Dampener: |
| ncluded |
| nlet Connection Position For Which Designed: |
| Horizontal |
| nlet Connection Device Type: |
| Stationary |
| Outlet Connection Position For Which Designed: |
| Horizontal |
| Outlet Connection Device Type: |
| Stationary |
| Alarm Signal: |
| Not included |
| Product Name: |
| Mark 2' retractable probe outline with tee and insertion/retraction tool |
| Special Features: |
| 3 in. Line size, fluid designed for: water; design pressure: 150 psig, hydrostatic pressure: 225 psig; ambient temp range: 40 degrees f to |
| 140 degf; includes integrally mounted hersey model 1050 transmitter |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| Γ134-t |
| |
| |