## NSN 6680-01-496-6860

Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-496-6860 **Overall Length:** 6.600 inches Media For Which Designed: Liquid **Inlet Connection Type:** Threaded **End Application:** Demineralized water unit **Integral Relief Valve:** Not included **Meter Type:** Piston/spring **Design Type:** Case **Unit Type:** Mounted **Scale Quantity:** 1 **Construction:** Inclosed w/sight window **Outlet Connection Type:** Threaded Scale Marking: Gpm or lpm Scale Type: Direct capacity reading **Mounting Method:** Direct line **Carrying Handle:** Not included **Dial Scale Marking Range:** +0.5/+5.0 Base: Not included **Integral Heat Source:** Not included **Maximum Working Pressure:** 6000.0 pounds per square inch **Maximum Water Capacity In Gallons Per Minute:** 

- -

**Maximum Air Capacity In Cubic Feet Per Minute:** 

0.0

## NSN 6680-01-496-6860

Flow Rate Indicating Meter - Page 2 of 2



Dial Scale Reference Pointer:
Not included
Integral Pulsation Dampener:
Not included
Inlet Connection Position For Which Designed:
Horizontal or vertical
Inlet Connection Device Type:
Stationary
Outlet Connection Position For Which Designed:
Horizontal or vertical
Outlet Connection Device Type:
Stationary
Alarm Signal:
Not included
Special Features:
Nha front panel assembly, for caustic and corrosive liquids, t316 stainless body, piston and cone, polycarbonate guard, temp range: -20
to 240 degrees f, port size: 1/2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T134-t