Flow Rate Indicating Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6680-01-499-5047

1	1.810 inches
h	nlet Connection Type:
F	lange
E	Ind Application:
N	Neter flow water
lı	ntegral Relief Valve:
Ν	lot included
N	Neter Type:
F	loat
C	Design Type:
C	Case
ι	Jnit Type:
N	Nounted
S	Scale Quantity:
1	
C	Construction:
h	nclosed w/sight window
C	Dutlet Connection Type:
F	lange
F	loat Quantity:
1	
N	Nounting Method:
C	Direct line
C	Carrying Handle:
Ν	lot included
C	Dial Scale Marking Range:
+	0.0/+35.2
E	Base:
Ν	lot included
F	loat Type:
C	Guided
F	loat Material:
S	Steel, stainless
0	Guide Type:
S	Solid rod
h	ntegral Heat Source:
Ν	lot included
C	Dial Scale Reference Pointer:
h	ncluded

NSN 6680-01-499-5047

Flow Rate Indicating Meter - Page 2 of 2



Integral Pulsation Dampener:		
-		
Not included		
Inlet Connection Position For Which Designed:		
Vertical		
Outlet Connection Position For Which Designed:		
Vertical		
Alarm Signal:		
Not included		
Special Features:		
Flow rate indicator provided by magnetic coupling		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		
Fiig:		
T134-t		